

FUSION NEON 1010 DUAL 10W/M 4000K IP67

NGA/LL/NF/1010/VH/10/4000/67

LED SPECIFICATION SHEET

PRODUCT DESCRIPTION



This Low Output Neon Flex features a square cross-section and is designed for adaptability and visual elegance. It's dual-bend design enables multi-directional bending, providing smooth, uniform illumination ideal for accent lighting and creative design applications.

PRODUCT NOTES

- Fusion Neon is typically supplied in custom cut lengths, but can also be supplied in reels up to a maximum length of 5m, with cables at both ends.

- The product is supplied with 5 mounting accessories per meter as standard, or available with an aluminium mounting channel upon request.

- When unreeling NGA's Neon Flex, two people must work together no more than 1.5 m apart. One supports the reel while the other feeds the Neon out for installation. This prevents twisting and protects the internal LEDs.



TECHNICAL INFORMATION

Product Code	NGA/LL/NF/1010/VH/10/4000/67
Product Group	Neon Flex
Bend Direction	Dual
Power Consumption	10W/m
Supply Voltage	24V DC Constant Voltage
Lumen Output	847 lm
Efficacy	85lm/W
Colour Temperature	4000K
CRI	Ra>90
MacAdam Step	<3SDCM
Lifetime	50000hrs
Cutting Interval	55.6mm

Dimensions	W 10mm x H 10mm
Mounting Clip Dims.	L 20mm x W 11.7mm x H 13mm
Alternative Mounting	1m Channel / Bendable Channel
Bending Diameter	V: $\varnothing \geq 100\text{mm}$ H: $\varnothing \geq 150\text{mm}$
Cable Entry	End / Side / Rear
Max Run Length	4m
Control Gear	On-Off / TRIAC / 0-10 / DALI / DMX
IP Rating	IP67
IK Rating	IK08
Operating Temperature	-40°C to 55°C
Beam Angle	120°
Protection Class	III

EUROPE & AMERICA HQ
T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ
T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA